

2 Hole Security Screws

Manufactured in A2 Stainless Steel

Suitable for internal and external applications

Screws have 2 small holes drilled into the head, therefore they can be removed by using unique 2 pin driver

Available in self tappers, machine screws, countersunk and pan head

Box Quantity 100

Countersunk Self Tappers AB Type Thread

Length		3/8"	1/2"	5/8"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	Driver
Dia		9.5mm	13mm	16mm	19mm	25mm	32mm	38mm	50mm	63mm	
4g	2.9mm	●	●		●	●	●	●			TH3
6g	3.5mm	●	●	●	●	●	●	●	●		TH4
8g	4.2mm	●	●	●	●	●	●	●	●		TH5
10g	4.8mm		●	●	●	●	●	●	●	●	TH6
12g	5.5mm					●		●	●		TH7
14g	6.3mm			●	●	●	●	●	●		TH8



Pan Head Self Tappers AB Type Thread

Length		3/8"	1/2"	5/8"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	Driver
Dia		9.5mm	13mm	16mm	19mm	25mm	32mm	38mm	50mm	63mm	
4g	2.9mm	●	●	●	●	●		●			TH3
6g	3.5mm	●	●	●	●	●	●	●	●		TH4
8g	4.2mm	●	●	●	●	●	●	●	●		TH5
10g	4.8mm	●	●	●	●	●	●	●	●	●	TH6
12g	5.5mm		●						●		TH7
14g	6.3mm			●	●	●	●	●	●		TH8



Countersunk Machine Screws

Dia.	Length	10mm	12mm	16mm	20mm	25mm	30mm	35mm	40mm	Driver
M3		●	●	●			●			TH3
M4		●	●	●	●	●	●	●		TH4
M5			●	●	●	●	●	●		TH6
M6			●	●	●	●	●		●	TH8



Pan Head Machine Screws

Dia.	Length	6mm	10mm	12mm	16mm	20mm	25mm	30mm	35mm	40mm	Driver
M3			●	●	●						TH3
M4		●	●	●	●	●	●				TH5
M5				●	●	●	●	●			TH6
M6				●	●	●	●	●		●	TH8



Raised Countersunk Machine Screws

Dia.	Length	12mm	25mm	30mm	40mm	50mm	Driver
M3.5		●	●	●	●	●	TH4



Tamper Resistant Hex Socket Screws

Manufactured in A2 Stainless Steel

Suitable for internal and external applications

Screws have an internal pin within the standard socket aperture

This prevents the use of standard socket keys

Screws are virtually impossible to remove without the matching screwdriver

Box Quantity 100

Countersunk Self Tappers AB Type Thread

Length		3/8"	1/2"	5/8"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	Driver
Dia		9.5mm	13mm	16mm	19mm	25mm	32mm	38mm	50mm	63mm	
6g	3.5mm	●	●	●	●	●		●			H30
8g	4.2mm		●	●	●	●	●	●	●		H40
10g	4.8mm		●	●	●	●	●	●	●	●	H40
12g	5.5mm				●	●	●	●			H40
14g	6.3mm				●	●	●	●	●		H40



Button Head Self Tappers AB Type Thread

Length		3/8"	1/2"	5/8"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	Driver
Dia		9.5mm	13mm	16mm	19mm	25mm	32mm	38mm	50mm	63mm	
6g	3.5mm	●	●	●	●	●		●			H30
8g	4.2mm	●	●	●	●	●	●	●	●		H40
10g	4.8mm		●	●	●	●	●	●	●	●	H40
12g	5.5mm				●	●	●	●			H40
14g	6.3mm				●	●	●	●	●		H40



Countersunk Machine Screws

Dia.	Length	8mm	10mm	12mm	16mm	20mm	25mm	30mm	40mm	50mm	60mm	Driver
M3			●	●	●							H20
M4		●	●	●	●	●	●	●	●			H40
M5			●	●	●	●	●	●	●	●	●	H40
M6		●	●	●	●	●	●	●	●	●	●	H40
M8				●	●	●	●	●	●	●	●	H50
M10						●	●	●	●	●	●	H60



Button Head Machine Screws

Dia.	Length	10mm	12mm	16mm	20mm	25mm	30mm	40mm	50mm	60mm	100mm	Driver
M3		●	●	●								H20
M4		●	●	●	●	●	●	●				H40
M5		●	●	●	●	●	●	●	●	●		H40
M6		●	●	●	●	●	●	●	●	●		H40
M8			●	●	●	●	●	●	●	●		H50
M10				●	●	●	●	●	●	●	●	H60
M12					●	●	●	●				H80



Raised Countersunk Machine Screws

Dia.	Length	12mm	20mm	25mm	30mm	40mm	50mm	60mm	Driver
M3.5		●	●	●	●	●	●	●	H30



6 Lobe / Resistorx Security Screws

Manufactured in A2 Stainless Steel

Suitable for internal and external applications

Screws have Star Drive with internal pin

Screws are virtually impossible to remove without the matching screwdriver

Box Quantity 100

Countersunk Self Tappers AB Type Thread

Dia	Length	1/2"	5/8"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	Driver
		13mm	16mm	19mm	25mm	32mm	38mm	50mm	63mm	75mm	
6g	3.5mm	●		●	●		●				T15
8g	4.2mm	●	●	●	●	●	●	●			T20
10g	4.8mm	●		●	●	●	●	●			T25
12g	5.5mm				●	●	●	●	●	●	T27
14g	6.3mm			●	●	●	●	●			T30



Button Head Self Tappers AB Type Thread

Dia	Length	3/8"	1/2"	5/8"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	Driver
		13mm	16mm	19mm	25mm	32mm	38mm	50mm	63mm	75mm		
6g	3.5mm		●		●	●		●				T10
8g	4.2mm	●	●	●	●	●	●	●	●			T15
10g	4.8mm		●		●	●	●	●	●			T25
12g	5.5mm					●	●	●	●	●	●	T27
14g	6.3mm				●	●	●	●	●			T27



Countersunk Machine Screws

Dia.	Length	6mm	8mm	10mm	12mm	16mm	20mm	25mm	30mm	40mm	50mm	Driver
M3		●	●	●	●	●	●					T10
M4				●	●	●	●	●	●			T20
M5				●	●	●	●	●	●	●	●	T25
M6				●	●	●	●	●	●	●	●	T30
M8					●	●	●	●	●	●	●	T40



Button Head Machine Screws

Dia.	Length	6mm	8mm	10mm	12mm	16mm	20mm	25mm	Driver
M3		●	●	●	●	●	●		T10
M4			●	●	●	●	●	●	T20
M5				●	●	●	●	●	T25
M6				●	●	●	●	●	T30
M8					●	●	●	●	T40
M10						●	●		T45



Button Head Machine Screws

Dia.	Length	30mm	40mm	50mm	60mm	80mm	100mm	Driver
M4		●						T20
M5		●	●	●				T25
M6		●	●	●				T30
M8		●	●	●				T40
M10		●	●	●	●	●		T45



Raised Countersunk Machine Screws

Dia.	Length	12mm	20mm	25mm	30mm	40mm	50mm	Driver
M3.5		●	●	●	●	●	●	T10



Clutch Head Screws

Manufactured in A2 Stainless Steel
 Suitable for internal and external applications
 Screws only operate in clockwise motion
 Ideal permanent fixing
 Installed with standard slotted screwdriver
 Box Quantity 100

Countersunk Self Tappers AB Type Thread

Dia	Length	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	Removal Tool
		13mm	16mm	25mm	32mm	38mm	50mm	
6g	3.5mm		●	●				RT41
8g	4.2mm	●	●	●	●	●	●	RT51
10g	4.8mm			●	●	●	●	RT61



Button Head Self Tappers AB Type Thread

Dia	Length	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	Removal Tool
		13mm	16mm	25mm	32mm	38mm	50mm	
6g	3.5mm	●	●	●				RT41
8g	4.2mm	●	●	●	●	●	●	RT51
10g	4.8mm	●	●	●	●	●	●	RT61
14g	6.3mm	●	●	●		●		RT61



Security Grille Anchor (Drill Out)



8.8 Grade Yellow Passivated Steel
 Will fix material up to 30mm to masonry
 Simply fix anchor then drill out socket removing hexagon flats
 Leaves permanent secure fixing

Drill Out

	65mm	70mm	Hole Dia.	Drill Out	Driver
M8	●		14mm	6mm	5mm Hex
M10		●	16mm	7mm	6mm Hex

Armour Rings

Available in Plated Steel or Stainless Steel
 Simple conical collar makes standard bolts and nuts tamperproof



Dia	M6	M8	M10	M12	M16
O/D	16mm	20mm	26mm	34mm	42mm
Thickness	7mm	8mm	10mm	13mm	16mm

Security Grille Anchor (Hex Socket Pin)



10.9 Grade Yellow Passivated Steel
 Will fix material up to 30mm to masonry
 Useful option where anchor needs to be removed
 Installed or removed with HSP Insert Bit

Hex Socket Pin

	65mm	70mm	Driver	Hole Dia
M8	●		5mm HSP	14mm
M10		●	6mm HSP	16mm

Security Tools

Description
Standard Magnetic Hand Drivers 1/4" Hex Drive
Ratchet Magnetic Hand Drivers 1/4" Hex Drive
2 Hole 1/4" Hex Insert Bits TH3,4,5,6,7,8
Hex Socket Pin 1/4" Hex Insert Bits H20,30,40,50,60,80
Hex Socket Pin 1/4" Key Wrench H20,30,40,50,60,80
6 Lobe Pin 1/4" Hex Insert Bits T15,20,25,27,30,40,45
6 Lobe Pin 1/4" Key Wrench T15,20,25,27,30,40,45
1/4" Socket Set Adaptor
3/8"-1/4" Drive Adaptor
1/2"-3/8" Drive Adaptor
Clutch Head Removal Tool RT41 6+8g, RT51 8+10g, RT61 12+14g
Security Grille Anchor 1/4" Hex Insert Bits 5mm, 6mm, 5mm HSP, 6mm HSP